


APPLITEC

TOOLING-Line



APPLITEC
SWISS TOOLING



TOOLING-Line

Porte-molettes

Rändelhalter

Knurl holders

1402 / 2402




A x B	L	E	D	C	A/2	Art. N°	Art. N°
6 x 6	132	2	3	10	3	1402-623	2402-623
6 x 6	132	3	3	10	3	1402-633	2402-633
7 x 7	140	2	3	10	3.5	1402-723	2402-723
7 x 7	140	3	3	10	3.5	1402-733	2402-733
7 x 7	140	4	3	10	3.5	1402-743	2402-743
7 x 7	140	2	4	10	3.5	1402-724	2402-724
7 x 7	140	3	4	10	3.5	1402-734	2402-734
7 x 7	140	4	4	10	3.5	1402-744	2402-744
8 x 8	140	2	3	10	4	1402-823	2402-823
8 x 8	140	3	3	10	4	1402-833	2402-833
8 x 8	140	4	3	10	4	1402-843	2402-843
8 x 8	140	2	4	10	4	1402-824	2402-824
8 x 8	140	3	4	10	4	1402-834	2402-834
8 x 8	140	4	4	10	4	1402-844	2402-844
10 x 10	150	3	3	10	5	1402-1033	2402-1033
10 x 10	150	4	3	10	5	1402-1043	2402-1043
10 x 10	150	3	4	10	5	1402-1034	2402-1034
10 x 10	150	4	4	10	5	1402-1044	2402-1044
10 x 10	150	5	4	10	5	1402-1054	-
12 x 12	150	4	4	12	6	1402-1244	2402-1244
12 x 12	150	5	4	12	6	1402-1254	2402-1254
12 x 12	150	4	5	12	6	1402-1245	2402-1245
12 x 12	150	5	5	12	6	1402-1255	2402-1255
16 x 16	150	4	4	12	8	1402-1644	2402-1644
16 x 16	150	4	5	12	8	-	2402-1645
16 x 16	150	5	5	12	8	-	2402-1655
16 x 16	150	6	4	12	8	-	2402-1664
16 x 16	150	6	6	12	8	-	2402-1666
16 x 16	150	8	6	12	8	-	2402-1686

Molettes en métal dur


Vollhartmetall Rändelrädchen

Solid carbide knurling wheels


1107



AA



BL



BR



GE

Molettes standards Standard Rändelrädchen Standard knurls	D1	E	D2	Pas (tous les 0.1 mm) Teilung (alle 0.1 mm) Pitch (every 0.1 mm)	
AA (0°)	8	2	3	0.2 - 0.6	
	8	2	4	0.2 - 0.6	
	8	3	3	0.2 - 0.6	
	8	3	4	0.2 - 0.6	
	8	4	3	0.2 - 0.6	
	8	4	4	0.2 - 0.6	
	10	2	3	0.2 - 0.8	
	10	2	4	0.2 - 0.8	
	10	3	3	0.2 - 0.8	
	BL 15° / BR 15° BL 30° / BR 30° BL 45° / BR 45°	10	3	4	0.2 - 0.8
		10	4	3	0.2 - 0.8
		10	4	4	0.2 - 0.8
	GE 30° GE 45°	12	4	4	0.3 - 1.0
		15	4	4	0.4 - 1.0
		15	4	5	0.4 - 1.0
		15	5	4	0.4 - 1.0
		15	5	5	0.4 - 1.0
		20	4	5	0.5 - 1.2
20		5	5	0.5 - 1.2	
20		6	6	0.5 - 1.2	
20	8	6	0.5 - 1.2		

Molettes "Quick" "Quick"-Rändelrädchen "Quick"-knurling wheels	D1	E	D2	Pas (tous les 0.1 mm) Teilung (alle 0.1 mm) Pitch (every 0.1 mm)
AA (0°)	8.9	2.5	4	0.2 - 0.8
BL 15° / BR 15°	14.5	3	5	0.4 - 1.0
BL 30° / BR 30°	21.5	5	8	0.5 - 1.2

Exécutions spéciales sur demande
Sonderausführungen auf Anfrage
Special executions on request

PERFORMANCE | PRECISION | RIGIDITY



SWISS MADE



APPLITEC
SWISS TOOLING

Applitec Moutier S.A.
Ch. Nicolas-Junker 2
CH-2740 Moutier

Tél. +41 32 494 60 20
Fax +41 32 493 42 60
www.applitec-tools.com